

P5 - 2500

START BOOSTER

12V

AGM

LED CHARGE INDICATOR

The test button allows users to easily check the charge level of the booster and test the alternator of a vehicle.



Model
P5-2500

Volts
12V

Peak Amps (A)
2500A

Of Batteries
1

Location of Fuse
Positive clamp

Fuse (A)
500

Dimensions (cm)
37x32x16

Cable Ø (mm2)
25

Cable Length (cm)
140

Unit Weight (KG)
11.3

Charger Voltage (V)
14.4

Charger Amps (A)
3

Vehicle types



ULTRA HIGH GRADE CABLES

Full copper woven cables are extremely durable and allow for very limited losses providing the highest starting power.

RIBBED ABS CHASSIS

Reinforced internal structure provides strength and durability making a dependable chassis.



www.lemania-energy.com

LEMANIAENERGY
Switzerland +

P5 - 3100

START BOOSTER

12V



LED CHARGE INDICATOR

The test button allows users to easily check the charge level of the booster and test the alternator of a vehicle.



Model
P5-3100

Volts
12V

Peak Amps (A)
3100A

Of Batteries
1

Location of Fuse
Positive clamp

Fuse (A)
500

Dimensions (cm)
37x32x16

Cable Ø (mm2)
25

Cable Length (cm)
140

Unit Weight (KG)
12.8

Charger Voltage (V)
14.4

Charger Amps (A)
3

Vehicle types



ULTRA HIGH GRADE CABLES

Full copper woven cables are extremely durable and allow for very limited losses providing the highest starting power.

RIBBED ABS CHASSIS

Reinforced internal structure provides strength and durability making a dependable chassis.



LEMANIAENERGY
Switzerland +