

H15-15-720

HYBRID BOOSTER

12V

ACM



The Hybrid is a combination of the highest quality starting batteries and the most powerful UltraCapacitors. Hybrids provide Ultra High starting current and extended cranking duration creating the perfect mix for professionals. These powerful boosters combine the best features of our technologies.

REVERSE POLARITY ALARM

This audible and visual alert informs professionals of incorrect terminal connections.

ON/OFF SWITCH

This model is fitted with an easy to use on off switch for maximum safety.

LED CHARGE INDICATOR

The test button allows users to easily check the charge level of the booster and test the alternator of a vehicle.



Model
H15-15-720

Volts
12V

Peak Amps (A)
2400

Farads (F)
5x720

Of Batteries
1

Location of Fuse
Clamp

Fuse (A)
500

Dimensions (cm)
38x32x24

Cable Ø (mm2)
25

Cable Length (cm)
154

Unit Weight (KG)
9.6

Charger Voltage (V)
14.4

Charger Amps (A)
3

Vehicle types



www.lemania-energy.com



H15-15-1500

HYBRID BOOSTER

12V

AGM



REVERSE POLARITY ALARM

This audible and visual alert informs professionals of incorrect terminal connections.

ON/OFF SWITCH

This model is fitted with an easy to use on off switch for maximum safety.

LED CHARGE INDICATOR

The test button allows users to easily check the charge level of the booster and test the alternator of a vehicle.



Model
H15-15-1500

Volts
12V

Peak Amps (A)
7500

Farads (F)
5x1500

Of Batteries
1

Location of Fuse
Clamp

Fuse (A)
500

Dimensions (cm)
38x32x24

Cable Ø (mm2)
25

Cable Length (cm)
154

Unit Weight (KG)
13

Charger Voltage (V)
14.4

Charger Amps (A)
3

Vehicle types



www.lemania-energy.com

LEMANIAENERGY
Switzerland +

H15-22-720

HYBRID BOOSTER

12V



REVERSE POLARITY ALARM

This audible and visual alert informs professionals of incorrect terminal connections.

LED CHARGE INDICATOR

The test button allows users to easily check the charge level of the booster and test the alternator of a vehicle.

ON/OFF SWITCH

This model is fitted with an easy to use on off switch for maximum safety.



Model
H15-22-720

Volts
12V

Peak Amps (A)
4000

Farads (F)
5x720

Of Batteries
1

Location of Fuse
Clamp

Fuse (A)
500

Dimensions (cm)
38x32x24

Cable Ø (mm2)
25

Cable Length (cm)
154

Unit Weight (KG)
12

Charger Voltage (V)
14.4

Charger Amps (A)
3

Vehicle types



H15-22-950

HYBRID BOOSTER

12V

ACM

CAP

REVERSE POLARITY ALARM

This audible and visual alert informs professionals of incorrect terminal connections.

ON/OFF SWITCH

This model is fitted with an easy to use on off switch for maximum safety.

LED CHARGE INDICATOR

The test button allows users to easily check the charge level of the booster and test the alternator of a vehicle.



Model
H15-22-950

Volts
12V

Peak Amps (A)
6000

Farads (F)
5x950

Of Batteries
1

Location of Fuse
Clamp

Fuse (A)
500

Dimensions (cm)
38x32x24

Cable Ø (mm2)
25

Cable Length (cm)
154

Unit Weight (KG)
12

Charger Voltage (V)
14.4

Charger Amps (A)
3

Vehicle types



LEMANIA ENERGY
Switzerland +