

P10-2500

START BOOSTER

12V

AGM

LED CHARGE INDICATOR

The test button allows users to easily check the charge level of the booster and test the alternator of a vehicle.

RIBBED ABS CHASSIS

Reinforced internal structure provides strength and durability making a dependable chassis.



Model
P10-2500

Volts
12V

Peak Amps (A)
2500

Of Batteries
1

Location of Fuse
Optional

Fuse (A)
Optional

Dimensions (cm)
32X28X14

Cable Ø (mm2)
25

Cable Length (cm)
55

Unit Weight (KG)
9.5

Charger Voltage (V)
14.4

Charger Amps (A)
3

Vehicle types



ULTRA HIGH GRADE CABLES

Full copper woven cables are extremely durable and allow for very limited losses providing the highest starting power.



LEMANIAENERGY
Switzerland +

P10-3100

START BOOSTER

12V

AGM

LED CHARGE INDICATOR

The test button allows users to easily check the charge level of the booster and test the alternator of a vehicle.

RIBBED ABS CHASSIS

Reinforced internal structure provides strength and durability making a dependable chassis.



Model
P10-3100

Volts
12V

Peak Amps (A)
3100

Of Batteries
1

Location of Fuse
Optional

Fuse (A)
Optional

Dimensions (cm)
32X28X14

Cable Ø (mm2)
25

Cable Length (cm)
55

Unit Weight (KG)
10.5

Charger Voltage (V)
14.4

Charger Amps (A)
3

Vehicle types



ULTRA HIGH GRADE CABLES

Full copper woven cables are extremely durable and allow for very limited losses providing the highest starting power.

www.lemania-energy.com

LEMANIA ENERGY
Switzerland +