

P23 - 2500

START BOOSTER

ULTRA HIGH GRADE CABLES

Full copper woven cables are extremely durable and allow for very limited losses providing the highest starting power.

LED CHARGE INDICATOR

The test button allows users to easily check the charge level of the booster and test the alternator of a vehicle.

P27



Car SUV
MPV 4WD



Motorcycle

12V



AGM



P27 CHARGING STATION

Easy to use, it keeps the booster ready for use. Can also recharge external 6V or 12V batteries.

Model	Model
P27	P23-2500

Volts	Volts
6/12V	12V

Peak Amps (A)	Peak Amps (A)
-	2500

Starting Amps (A)	# Of Batteries
-	1

# Of Batteries	Location of Fuse
0	Clamp

Location of Fuse	Fuse (A)
-	500

Fuse (A)	Dimensions (cm)
-	33x15x31

Dimensions (cm)	Cable Dimenter (mm2)
40x18x31	25

Cable Dimenter (mm2)	Cable Length (cm)
-	84

Cable Length (cm)	Unit Weight (KG)
-	10

Unit Weight (KG)	Charger Voltage (V)
4	14.4

Charger Voltage (V)	Charger Amps (A)
230	2

Charger Amps (A)	
1.1-4	



LEMANIAENERGY
Switzerland +

www.lemania-energy.com