

P6 - 25000

START BOOSTER

12V

AGM

LED CHARGE INDICATOR

The test button allows users to easily check the charge level of the booster and test the alternator of a vehicle.

Optional LED clamps*



Model
P6-2500

Volts
12V

Peak Amps (A)
2500A

Of Batteries
1

Dimensions (cm)
30x26x14

Cable Ø (mm2)
25

Cable Length (cm)
72

Unit Weight (KG)
10

Charger Voltage (V)
14.4

Charger Amps (A)
3

Vehicle types



ULTRA HIGH GRADE CABLES
Full copper woven cables are extremely durable and allow for very limited losses providing the highest starting power.

RIBBED ABS CHASSIS
Reinforced internal structure provides strength and durability making a dependable chassis.



LEMANIA ENERGY
Switzerland +

P6 - 3100

START BOOSTER

12V

AGM

LED CHARGE INDICATOR

The test button allows users to easily check the charge level of the booster and test the alternator of a vehicle.

Optional LED clamps*



Model

P6-3100

Volts

12V

Peak Amps (A)

3100

Of Batteries

1

Dimensions (cm)

30x26x14

Cable Ø (mm2)

25

Cable Length (cm)

72

Unit Weight (KG)

11

Charger Voltage (V)

14.4

Charger Amps (A)

3

Vehicle types



ULTRA HIGH GRADE CABLES

Full copper woven cables are extremely durable and allow for very limited losses providing the highest starting power.

RIBBED ABS CHASSIS

Reinforced internal structure provides strength and durability making a dependable chassis.



LEMANIA ENERGY
Switzerland +