

P9 - 2500

START BOOSTER

12V

AGM

LED CHARGE INDICATOR

The test button allows users to easily check the charge level of the booster and test the alternator of a vehicle.



Model
P9-2500

Volts
12V

Peak Amps (A)
2500A

Of Batteries
1

Location of Fuse
Optional

Fuse (A)
Optional

Dimensions (cm)
33x35x25

Cable Ø (mm2)
25

Cable Length (cm)
100

Unit Weight (KG)
10

Charger Voltage (V)
14.4

Charger Amps (A)
3

Vehicle types



ULTRA HIGH GRADE CABLES
Full copper woven cables are extremely durable and allow for very limited losses providing the highest starting power.

RIBBED ABS CHASSIS
Reinforced internal structure provides strength and durability making a dependable chassis.

www.lemania-energy.com



LEMANIA ENERGY
Switzerland +

P9 - 3100

START BOOSTER

12V

AGM

LED CHARGE INDICATOR

The test button allows users to easily check the charge level of the booster and test the alternator of a vehicle.



Model

P9-3100

Volts

12V

Peak Amps (A)

3100

Of Batteries

1

Location of Fuse

Optional

Fuse (A)

Optional

Dimensions (cm)

33x35x25

Cable Ø (mm²)

25

Cable Length (cm)

100

Unit Weight (KG)

11.3

Charger Voltage (V)

14.4

Charger Amps (A)

3

Vehicle types



ULTRA HIGH GRADE CABLES

Full copper woven cables are extremely durable and allow for very limited losses providing the highest starting power.

RIBBED ABS CHASSIS

Reinforced internal structure provides strength and durability making a dependable chassis.



LEMANIAENERGY
Switzerland 

www.lemania-energy.com