

P11 - 2000

START BOOSTER

12V

AGM

LED CHARGE INDICATOR

The test button allows users to easily check the charge level of the booster and test the alternator of a vehicle.



Model
P11-2000

Volts
12V

Peak Amps (A)
2000A

Of Batteries
1

Location of Fuse
Optional

Fuse (A)
Optional

Dimensions (cm)
35x38x21.5

Cable Ø (cm2)
25

Cable length (cm)
178

Unit Weight (KG)
11

Charger Voltage (V)
14.4

Charger Amps (A)
3

Vehicle types



ULTRA HIGH GRADE CABLES

Full copper woven cables are extremely durable and allow for very limited losses providing the highest starting power.

RIBBED ABS CHASSIS

Reinforced internal structure provides strength and durability making a dependable chassis.



LEMANIA ENERGY
Switzerland +

www.lemania-energy.com

P11 - 25000

START BOOSTER

12V

AGM

LED CHARGE INDICATOR

The test button allows users to easily check the charge level of the booster and test the alternator of a vehicle.



Model
P11-2500

Volts
12V

Peak Amps (A)
2500A

Of Batteries
1

Location of Fuse
Optional

Fuse (A)
Optional

Dimensions (cm)
35x38x21.5

Cable Ø (cm2)
25

Cable length (cm)
178

Unit Weight (KG)
11.5

Charger Voltage (V)
14.4

Charger Amps (A)
3

Vehicle types



ULTRA HIGH GRADE CABLES

Full copper woven cables are extremely durable and allow for very limited losses providing the highest starting power.

RIBBED ABS CHASSIS

Reinforced internal structure provides strength and durability making a dependable chassis.



LEMANIAENERGY
Switzerland +

www.lemania-energy.com